



SIDE VIEW

**FRONT VIEW
(CABLE IS NOT SHOWN)**

NOTES:

- 1). UPRIGHT CONFIGURATION SHALL BE USED FOR MOUNTING ON MAST ARMS, SIGNAL HEAD FRAMEWORKS AND PEDESTALS.
- 2). UPRIGHT MOUNTING HARDWARE SHALL BE SUPPLIED BY THE CONTRACTOR.
- 3). TEFLON TAPE SHALL BE APPLIED TO THREADS BEFORE MOUNTING.
- 4). ROUTE THE LEAD-IN CABLE THROUGH THE METAL CAP AND THE RUBBER PLUG. REPLACE THE METAL CAP, SEALING THE CABLE ENTRY PORT. TIGHTEN THE METAL CAP SO THE CABLE WILL NOT SLIDE THROUGH THE RUBBER PLUG.

| | | | | | | | | |
|--|--|--------------------|---|--------------------------|-------------|----------|------------------------------|--------------------|
| | ENGINEERING SUPPORT RECOMMENDED | 09/01/2020 DATE | EMERGENCY PREEMPTION RECEIVER - UPRIGHT MOUNT | | | REVIEWED | DEPUTY DIRECTOR - DESIGN | 09/01/2020 DATE |
| | | | | STANDARD NO. T-14 (2020) | SHT. 1 OF 2 | APPROVED | CHIEF ENGINEER | 09/01/2020 DATE |