

Welcome

to the

ELKTON ROAD PLANNING STUDY

Maryland State Line To Delaware Avenue


Public Workshop



October 19, 2005



Project Development Process



List of Working Group Members

Roy Lopata - Newark Planning Department
Gerald Conway - Newark Police Department
Richard Armitage - University of Delaware
Eric Schwab - Town Court and Park Place
Tim Thompson - The Trap Restaurant
Willett Kempton - Newark Bicycle Committee
Nancy Rich - Beverley Road
Jill Bennett-Gaieski - Orchard Road
Doug Tuttle - Devon
Christopher J. Heck
 DuPont Stine-Haskell Research Center
Stephen D. Nash
 DuPont Stine-Haskell Research Center
Heather Dunigan - WILMAPCO
Gregory Meece - Newark Charter School
Marc Cote - DelDOT
Tom Brooks - DelDOT



ELKTON ROAD PLANNING STUDY

October 19, 2005



Project Goals

- **Pavement Reconstruction**
- **Capacity and Operational Improvements**
- **Safety Improvements**
- **Bicycle and Pedestrian Improvements**
- **Transit Facilities Improvements**



ELKTON ROAD PLANNING STUDY

October 19, 2005



Roadway Characteristics

Area 1 - Maryland State Line to SR 4

- 4 lane divided with 40 to 50 foot grass median
- 10 Foot Wide Shoulder on Both Sides
- Speed Limit – 50 mph
- Current Traffic Volume – 43,000 AADT



Area 2 - SR 4 to West Park Place

- 4 lane divided – 15 feet wide median
- 8~12 foot wide shoulder/bike path on WB Elkton Road
- Speed Limit – 35 ~ 40 mph
- Current Traffic Volume – 24,000 AADT




Area 3 – West Park Place to Delaware Avenue

- 4 lane un-divided
- No shoulders
- Speed Limit – 25 ~ 35 mph
- Current Traffic Volume - 19,000 AADT



Study Area Traffic Volume





ELKTON ROAD PLANNING STUDY

October 19, 2005



Summary of Capacity Analysis

INTERSECTION LEVEL OF SERVICE (LOS) : is a qualitative assessment of the operation of the intersection as measured by the average delay (seconds) per vehicle.



ELKTON ROAD PLANNING STUDY

October 19, 2005





LOS Table for Signalized Intersections

INTERSECTION LEVEL OF SERVICE (LOS) : is a qualitative assessment of the operation of the intersection as measured by the average delay (seconds) per vehicle.

Control Delay	
<u>LOS</u>	<u>per vehicle (sec)</u>
A	≤ 10
B	>10 - 20
C	>20 - 35
D	>35 - 55
E	>55 - 80
F	>80



Summary of Safety Analysis



Total Number of Crashes from May, 2001 through April, 2004



ELKTON ROAD PLANNING STUDY

October 19, 2005



Summary of Safety Analysis

- Reviewed 438 crash reports over 3 year period
- Crash Rate is higher than statewide average
- Most crashes (47%) are rear end type
- 30% were left turn and angle
- No fatalities during this time period

(However, before the reported crash period, there were 2 fatalities at Amstel Avenue and 1 fatality at Otts Chapel Road. All three were pedestrian/bicycle related.)



Pedestrian and Bicycle Needs

Maryland State Line to SR 4


- No continuous sidewalks
- Shoulders used for bicycle traffic
- Ramps are not ADA compliant

SR 4 to West Park Place

- 4-10 foot discontinuous bike lane on eastbound side
- 8~12 foot continuous bike lane on westbound side
- Sidewalk everywhere except south of Elkton Road from SR 4 to Gravenor Lane
- Ramps are not ADA compliant

West Park Place to Delaware Avenue

- No eastbound bike lane east of Murray Road
- 8 foot bike lane on westbound side from Apple Road to West Park Place
- Continuous sidewalks on both sides
- Utility poles within sidewalk
- Multiple entrances hinder usage
- High pedestrian and bicycle activities
- Ramps are not ADA compliant



Transit Needs


Public Transit Route

- DART Route 6, 16, 33,39, 65
- Unicity Bus System Route N-1 and N-3
- University of Delaware Bus System: several routes



Bus Stop facilities

- Most of the bus stops have no bus pad or shelter
- Need for additional bus shelters



Area 1 - Maryland State Line to SR4

Alternative 1

Description

- Mainline - four lane section
- Off road bicycle/pedestrian path
- Double WB left turn lane at Otts Chapel Road
- Crosswalks and pedestrian signals
- On road bike lane

Pros

- No change in existing footprint of Elkton Road
- Improved bicycle/pedestrian mobility and Safety

Cons

- Unsatisfactory Level of Service (LOS) at SR 4 intersection
- Long queue on EB Elkton Road at Haskell Road (AM Peak)
- Long queue on NB Otts Chapel Road

Cost: \$30.3 million

Alternative 2

Description

- Mainline - six lane section from Otts Chapel Road to east of SR 4
- Off road bicycle/pedestrian path
- Double WB left turn lane at Otts Chapel Rd.
- Crosswalks and pedestrian signals
- On road bike lane
- Free flow right turn @ NB Otts Chapel

Pros

- Satisfactory Level of Service (LOS) at all intersections
- Reduction in EB Elkton Road queue length at Otts Chapel Road, Haskell Road and SR 4 intersection

Cons

- Greater right of way impact than other Alternatives

Preferred Alternative of Working Group

Cost: \$35.5 million

Alternative 3

Description

- Mainline - six lane section at SR 4 Intersection
- Crosswalks and pedestrian signals
- On road bike lane
- Off road bicycle/pedestrian path
- Double WB left turn lane at Otts Chapel Road


Pros

- Satisfactory Level of Service (LOS) at all intersections
- Minimum impact on median and right of way encroachment

Cons

- Long queues on NB Otts Chapel Road
- Long queue on EB Elkton Road at Haskell Road (AM Peak)

Cost: \$32.3 million



ELKTON ROAD PLANNING STUDY

October 19, 2005



Area 2 - SR4 to West Park Place

Alternative 1

Description

- Mainline - four lane section
- Add SB left turn at Casho Mill Road
- Close median at Chrysler Ave./ Lincoln Drive

Pros

- Increase mobility and access into town by adding left turn at Casho Mill Road

Cons

- Unsatisfactory Level of Service (LOS) at Casho Mill Road
- Does not reduce rear end and angle crashes at Casho Mill Road
- Long queue on WB Elkton Road at Casho Mill Road

Cost: \$16.8 million

Alternative 2

Description

- Mainline - four lane section
- Change phasing of signal at Casho Mill Road

Pros

- Reduce angle crashes at Casho Mill Road
- Improves capacity over existing condition

Cons

- Vehicles on Casho Mill Road SB right Turn will need to yield to pedestrians

Preferred Alternative of Working Group

Cost: \$16.8 million

Alternative 3

Description

- Same as Alternative 2
- Double EB left turn lane at Casho Mill Road


Pros

- Reduce the length of the EB left turn lane at Casho Mill Road
- Reduce angle crashes at Casho Mill Road

Cons

- Right of way and utility impacts at Casho Mill Road / Elkton road
- Short weaving distance on NB Casho Mill Road
- Shift of EB lanes into buffer along Gravenor Road will impact landscape screen
- Longer queue on NB Casho Mill Road at railroad crossing underpass

Cost: \$17.2 million



ELKTON ROAD PLANNING STUDY

October 19, 2005



Area 3 – W. Park Place to Delaware Ave.

Alternative 1

Description

- Mainline – three lane section with center turn lane from Apple Road to Amstel Ave.
- Reduce access points/prohibit WB left turn at Rittenhouse Road intersection
- SB and WB right turn lanes added to Apple Road/Elkton Road intersection

Pros

- Easy access to businesses
- Continuous 5' – 8' wide bike lane
- Wide median for pedestrian refuge provided at Amstel Road
- Travel speeds will be reduced
- Able to convert to 4-lane roadway in future if capacity needed

Cons

- Reduced capacity of Elkton Road between Apple Road and Amstel Avenue
- Long queue on westbound Elkton Road approaching Amstel Avenue intersection

Preferred Alternative of Working Group

Cost: \$13.0 million

Alternative 2

Description

- Mainline – two lane section with median and left turn lane from Apple Rd. to Amstel Ave.
- Reduce access points / prohibit WB left turn at Rittenhouse Road cross over
- SB and WB right turn lanes added to Apple Road /Elkton Road intersection

Pros

- Continuous 5' - 8' bike lane
- Wide median for pedestrian refuge provided at Amstel Road
- Increase aesthetics by planting trees/shrubs on median islands
- Travel speeds will be reduced

Cons

- Reduce capacity of Elkton Road between Apple Road and Amstel Ave.
- Limited access to businesses – cannot U-turn between Apple Road and Amstel Ave.
- Long queue on WB Elkton Road approaching Amstel Ave. intersection

Cost: \$12.8 million

Alternative 3

Description

- Mainline-four lane undivided (same as existing) eliminating 4' flush median between Apple Road and Amstel Ave.
- Provide 5' bike lane
- Reduce access points/prohibit WB left turn at Rittenhouse Road cross over
- SB and WB right turn lanes added to Apple Road/Elkton Road intersection

Pros

- Maintain existing roadway capacity of Elkton Road
- Continuous 5' wide bike lane
- Reduction in WB Elkton Road queue at Amstel Ave. intersection
- Minimum property impact

Cons

- Limited traffic calming/pedestrian safety improvement at Amstel Rd.
- Increased potential of speeding
- Left turn access to businesses occurs from thru lanes

Cost: \$12.9 million



ELKTON ROAD PLANNING STUDY

October 19, 2005

