



PLAN VIEW

NOTES:


- 1). TYPE 5 CONDUIT JUNCTION WELL SHALL BE PRECAST CONCRETE. AT LEAST ONE HOLE IN PRECAST WELLS WILL BE OF A 5" DIAMETER COMPLETELY THROUGH THE WALL. UNUSED HOLES SHALL BE PLUGGED.
- 2). ALL CONDUIT JUNCTION WELLS CONSTRUCTED SHALL BE WITHIN CONSTRUCTED FLUSH WITH THE SURFACE OF THE SAME. INSTALLATION IN UNPAVED AREAS WILL BE CONSTRUCTED ABOVE GRADE AND GRADED TO DRAIN AWAY FROM CONDUIT JUNCTION WELL.
- 3). ALL CRACKS, GAPS, OR OPENINGS IN JUNCTION WELL WALL SHALL BE SEALED WITH CONCRETE.



SECTION A-A



DETAIL "A"



SECTION B-B



DELAWARE
DEPARTMENT OF TRANSPORTATION

CONDUIT JUNCTION WELL, TYPE 5

STANDARD NO. T-1 (2012)

SHT. 3 OF 3

APPROVED

SIGNATURE ON FILE
CHIEF ENGINEER

01/07/2013
DATE

RECOMMENDED

SIGNATURE ON FILE
DESIGN ENGINEER

12/20/2012
DATE